









ADAPTABILITY AND MOBILITY

The **FMC-3** is the perfect access solution for light construction and restoration. This work platform distinguishes itself by its great adaptability, thanks to the built-in floor extensions of progressive lengths that allow an extension of the working area of up to 8 feet 6 inches (2,6 meters). For safety, these extensions can be locked and are provided with a non-slip material to avoid accidental falls

The FMC-3 uses a reliable and proven rack and pinion lift system. It is equipped with a Honda gasoline engine or with electrical motors

The FMC-3 can also be delivered with a trailer that makes it easier to move on the road and jobsite.

METRIC

1,2 M X 0,43 M X 0,07 M / 13,6 KG

MAXIMUM LENGTH OF PLATFORM W/ SINGLE MAST (DOUBLE)	33 FT (100 FT)	10 M (30,5 M)
MAXIMUM PAYLOAD (SINGLE MAST CONFIGURATION)	3 000 LB	1 100 KG
LIFTING SPEED	25 FT / MIN	7,5 M / MIN
MAXIMUM WIDTH OF WORKING AREA (WITH 5 FT FLOOR EXTENSIONS)	8 FT 6 IN	2,6 M
MAXIMUM HEIGHT	395 FT	120 M
STANDARD DISTANCE BETWEEN ANCHORS	25 FT	7 M
LIFTING SYSTEM	RACK AND PINION (MODULE 6)	
TYPES OF ENGINE	13 H.P. HONDA GASOLINE ENGINE (ELECTRICAL ALSO AVAILABLE)	
MOTORIZED UNIT DIMENSIONS (L X W X H) / WEIGHT	2 FT 6 IN X 3 FT X 4 FT 9 IN / 1 200 LB	1,36 M X 0,94 M X 1,44 M / 544 KG
MAST SECTION DIMENSIONS (L X W X H) / WEIGHT	17 3/4 IN X 17 3/4 IN X 5 FT / 170 LB	0,45 M X 0,45 M X 1,49 M / 77 KG
EXTENSION DIMENSIONS (L X W X H) / WEIGHT	5 FT 2 IN X 4 FT X 2 FT 11 IN / 230 LB	1,5 M X 1,2 M X 0,9 M / 104 KG

IMPERIAL

4 FT X 1 FT 5 IN X 3 IN / 30 LB

ANSI 92.9; CSA B354.7-17



STANDARD COMPLIANCE

FLOOR EXTENSION DIMENSIONS (L X W X H) / WEIGHT

TECHNICAL DATA

- + 1 800 267.0094
- + 1 450 658.0094
- + 1888 372.2648